

A201-6100 SILENCER

Super Critical Grade - 32 to 42 dB(A)
Improved attenuation over Legacy 201-6100 Silencer



APPLICATION

Excellent superior critical grade silencer providing a premium level of performance where ambient noise levels are very low and optimal attenuation is mandatory. Recommended for all marine, stationary, and mobile, power applications where noise attenuation is critical. The standardized A201-6100 is a more cost competitive offering than the legacy 201, while improving performance by up to 3% and even lowering volume by an average of 31%.


CONSTRUCTION


Heavy duty steel construction. Sizes 6" and below come standard with ID Cuff / OD Tube connections. Sizes 8" and above come standard with ANSI Flanged connections. Additional connections available. Call factory for details.

FINISH AND OPTIONAL MATERIALS

High heat powder coat on sizes 12" and smaller, and high heat black paint on sizes 14" and larger. Silencers available in stainless steel, or with aluminized heads and shell - call factory for details.

TYPICAL ATTENUATION CURVE A201-6100 OCTAVE BAND





Part Number	A Inlet Size	B Diameter	C OAL - I	D OAL - 2	E OAL - 3	F Min	F Max	G Flange-Center	H Min	H Max	WT
A201-6102	2	10	30	27	24	4	8	8	4	7	33
A201-61025	25	10	42	39	36	5	15	8	5	11	46
A201-6103	3	12	43	40	37	5	15	9	5	11	58
A201-61035	35	14	55	52	49	6	21	10	6	16	92
A201-6104	4	14	55	52	49	6	21	11	6	16	92
A201-6105	5	16	62	58	54	7	23	12	7	17	118
A201-6106	6	20	75	71	67	8	30	14	8	22	184
A201-6108	8	24	76	72	68	10	30	16	10	21	283
A201-6110	10	28	100	96	93	11	42	18	11	22	499
A201-6112	12	36	102	99	95	14	40	22	14	33	749
A201-6114	14	36	138	135	132	15	61	22	15	46	1021
A201-6116	16	42	140	137	133	16	60	25	16	46	1243
A201-6118	18	48	142	139	135	18	59	29	18	46	1541
A201-6120	20	48	165	162	159	19	72	29	19	55	1773
A201-6122	22	54	166	163	161	21	71	32	21	52	2045
A201-6124	24	60	167	164	162	23	70	35	23	55	2335

Sizes 6" and below come standard with ID Cuff / OD Tube connections.

Sizes 8" and above come standard with ANSI Flanged connections.

All spatial dimensions are in inches. Inlet sizes available up to 30.0 inches.

PRICES

Additional connections available. See Silencer Price Book pg. 48 for breakdown of A200 part number. F MAX is for inlet only. H MAX is for outlet only. All weights are in pounds. All weights are approximate. Use diameter to find bracket sizes. Example: A201-6108 (24" dia) would require 28-2400 brackets (or similar 29 brackets).